

R-LinX

The clever little alarm handler, capable of sending alerts to your two-way radio, smartphone, email and workstation alert.



4x Onboard Contact Closures (Easily expandable to 12 via a Brainbox ED-588 GPIO module)

4x USB 2.0 Ports



Power Consumption: +5V DC, 2.6 Amps
Dimensions: 120mm x 110mm x 23mm
Din Rail Mountable

Technical Specifications

CPU type / Speed	Quad Core ARM Processor / 1.2GHz
RAM	1GB LPDDR2 SRAM
Integrated Wi-Fi	2.4GHz 802.11 ac b/g/n
Ethernet speed	10/100 Mbps
CONNECTIONS	
USB Ports	4 (non-user configurable)
Contact Closure I/P	4
Serial Port	RS232 / RS485 (user selectable)
DMR Connection	
Motorola	Fixed Mobile
Hytera	Fixed Mobile or Repeater (excluding ONE)
Escalation stage:	
ONE	1
ALERT	3
COMPLETE	3
Voice Alert Output	YES (required ED588, Fixed Mobile only)
Data Logging	YES (USB Pendrive supplied)
SMS Output	YES (Via approved D-Link SMS Dongle)
SMS Input	YES (Via approved D-Link SMS Dongle)
Email Output	YES
TCP I/P	YES
Workstation Alert Output	YES
Lone Worker:	
ONE	N/A
ALERT	N/A
COMPLETE	10
PHYSICAL	
Power	+5Vdc, 2.6Amps
Dimensions	120mm x 110mm x 23mm