

TLK 25 Wi-Fi

Wearable Communications Device





Let's TLK

Communicate and operate confidently with TLK 25 Wi-Fi, a wearable WAVE PTX device that expands your capabilities beyond push-to-talk and doesn't limit your range. Compact, powerful, rugged and equipped with an intuitive voice assistant for seamless communications, the TLK 25 Wi-Fi is designed for efficiency. Access a safety and security ecosystem in a small, intelligent device with just your Wi-Fi network.



Small, sleek and smart

- Lightweight, wearable design
- Durable meets discreet
- Shaped for safety



Intuitive voice assistance

- Communications
- Device settings
- Safety features
- Statuses
- Notifications and alerts



Packaged ecosystem

- Wi-Fi based and flexible
- Dedicated emergency features
- WAVE PTX ecosystem
- TLK Configuration App







Device specifications

| GENERAL SPECIFICATIONS | | | | | |
|--|---|--|--|--|--|
| Network | 2.4, 5 GHz Wi-Fi | | | | |
| Channel Capacity | 96 Channels | | | | |
| Contact List | 300 Contacts | | | | |
| Dimensions | 3.2 x 1.9 x 0.7 in (82 x 48 x 18.7mm) | | | | |
| Weight (with Embedded Battery) | 2.6 oz (73g) | | | | |
| Battery Capacity | 1260mAh | | | | |
| Battery (Type Battery) Operating Hours 5:5:90 Duty Cycle | 12 hours | | | | |
| IP Rating | IP67 | | | | |
| Ports | USB Type-C (use for charging) 3.5mm audio jack | | | | |
| Sensor | Accelerometer | | | | |
| Apps | Powered by WAVE PTX | | | | |
| Encryption | AES 256 | | | | |
| | | | | | |

OPUS

+1, -3

115 dB SPL

<1%

| WIFI SPECIFICATIONS | | | | | | |
|-------------------------------|--|--|--|--|--|--|
| Frequency Range | 2.4 GHz, 5 GHz | | | | | |
| Standards Supported | 802.11 a, b, g, n, ac | | | | | |
| Security Protocol Supported | WPA2 (personal and enterprise), WPA3 (personal) | | | | | |
| Maximum Number of SSIDs | 5 | | | | | |
| | | | | | | |
| BLUETOOTH | | | | | | |
| Version | 5.0 LE | | | | | |
| Range | 10m | | | | | |
| Supported Profiles | HSP, SPP, GATT | | | | | |
| Simultaneous Audio Connection | 1 | | | | | |

| ENVIRONMENTAL SPECIFICATIONS | | | | |
|---|--|--|--|--|
| -20°C to 60°C (radio) -10°C to 60°C (with battery) | | | | |
| -40°C to 85°C | | | | |
| Per MIL-STD | | | | |
| Per MIL-STD | | | | |
| Per MIL-STD | | | | |
| IP67 | | | | |
| Per MIL-STD | | | | |
| | | | | |

MILITARY STANDARDS (MIL-STD-810)

AUDIO SPECIFICATIONS

Audio Distortion at Rated Audio

Digital Vocoder Type Audio Response

Maximum Speech

Loudness by Default¹

| | MIL STD0100 | | MIL-STD810D | | MIL-STD 810E | | MIL-STD 810F | | MIL-STD 810G | | MIL-STD 810H | |
|----------------------------|-------------|------------------|-------------|----------------------|--------------|-----------------------|--------------|----------------------|--------------|----------------------|--------------|----------------------|
| | MIL-STD810C | | WIL-SID8IUD | | WIL-STD 810E | | WIL-STD 810F | | MIL-STD 810G | | WIL-SID 810H | |
| | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure | Method | Procedure |
| Low Pressure | 500.1 | I | 500.2 | II | 500.3 | | 500.4 | 11 | 500.6 | | 500.6 | II |
| High Temperature | 501.1 | I, II | 501.2 | I/A1, II/A1 | 501.3 | I/A1, II/A1 | 501.4 | I/Hot, II/ Hot | 501.6 | I/A1, II/A1 | 501.7 | I/A1, II/A1 |
| Low Temperature | 502.1 | I | 502.2 | I, II | 502.3 | I, II | 502.4 | I, II | 502.6 | I, II | 502.7 | I, II |
| Temperature Shock | 503.1 | Ι | 503.2 | A1/C3 | 503.3 | A1/C3 | 503.4 | I | 503.6 | I-C | 503.7 | I-C |
| Solar Radiation | 505.1 | II | 505.2 | I/A1 | 505.3 | I/A1 | 505.4 | I/A1 | 505.6 | I/A1 | 505.7 | I/A1 |
| Rain | 506.1 | I, II | 506.2 | I, II | 506.3 | I, II | 506.4 | I, III | 506.6 | I, III | 506.6 | I, III |
| Humidity | 507.1 | Ш | 507.2 | Ш | 507.3 | II | 507.4 | - | 507.6 | ll/ Aggravated | 507.6 | ll/ Aggravated |
| Salt Fog | 509.1 | I | 509.2 | | 509.3 | I | 509.4 | - | 509.6 | - | 509.7 | - |
| Blowing Dust & Sand | 510.1 | I/- | 510.2 | I, II | 510.3 | I, II | 510.4 | I, II | 510.6 | I, II | 510.7 | I, II |
| Vibration | 514.2 | VIII/CatF, XI | 514.3 | I/Cat10, II/ Cat3 | 514.4 | I/Cat10, III/ Cat3 | 514.5 | I/Cat24, II/ Cat5 | 514.7 | I/Cat24, II/ Cat5 | 514.8 | I/Cat24, II/ Cat5 |
| Shock | 516.2 | I, II | 516.3 | I, IV | 516.4 | I, IV | 516.5 | I, IV | 516.7 | I, IV | 516.8 | I, IV |
| Contamination by Fluids | | | | | | | | | 504.2 | II | 504.3 | 2.2.6b |

¹ Loudness performance based on TLK 25 paired with PMLN8536



Wear your TLK 25 the way you want



Badge clip: PMLN8538

High quality audio and operational experiences: TLK 25 Earpiece

Featuring PTT and voice assistant buttons, TLK 25's included compatible earpiece allows users to leave their device in their pocket while still performing key device functions. TLK 25 is also Bluetooth 5.0 LE compatible, giving users the ability to use bluetooth earpieces or headphones while providing better range and connectivity, clearer listening and power efficiency.

Holster: PMLN8537

USB-C charging cable: PMKN4294 Magnetic multi-unit charger (MUC): PMPN4660 Wall mount bracket for MUC: BR000638A01



To learn more, visit: www.motorolasolutions.com/tlk25



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. motorolasolutions.com

Available in the United States and Europe.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. ©2024 Motorola Solutions, Inc. All rights reserved. 01-2024 [CK04]